



ALUMINIUM PIPE STOPPER

Available for internal pipe diameters from 1,5"

The test stopper are made of cast aluminium. The expandable natural rubber ring ensures optimum sealing of the pipe. They are suitable for closing and sealing pipes during the forming process and for sealing in low-pressure applications.

- Extra long wing nuts for easy handling
- Hollow spindle for gas connection in forming applications
- Plastic cap closes the spindle for pipe seal measurements
- Cost effective solution
- Temperature resistant from -30 °C to +90 °C

Part No.	ID mm	OD Stopper		Outer thread Inch	Max. counter- pressure bar	Weight kg
		Inch	mm			
RG350150	38 - 50	1 1/2	40	1/2	2,0	0,17
RG350151	49 - 62	2	50	1/2	2,0	0,22
RG350152	62 - 77	2 1/2	65	1/2	2,0	0,27
RG350153	73 - 89	3	75	1/2	1,3	0,31
RG350154	84 - 103	3 1/2	90	1/2	1,0	0,36
RG350155	94 - 110	4	100	1/2	0,6	0,36

Part No.	ID mm	OD Stopfen		Outer thread Inch	Max. counter- pressure bar	Weight kg
		Inch	mm			
RG350156	112 - 130	4 1/2	115	1/2	0,69	0,47
RG350157	125 - 142	5	125	1/2	0,69	0,79
RG350158	146 - 168	6	150	1/2	0,69	0,70
RG350159	175 - 200	7	175	1	0,48	1,92
RG350160	193 - 220	8	200	1	0,48	1,59
RG350161	220 - 240	9	225	1	0,48	2,06
RG350162	245 - 270	10	250	1	0,48	2,52
RG350163	274 - 328	11	275	1	0,48	3,45
RG350164	295 - 325	12	300	1	0,48	3,42
RG350165	325 - 360	13	325	1	0,34	4,75
RG350166	350 - 385	14	350	1	0,34	6,95
RG350167	370 - 410	15	375	1	0,34	5,35
RG350168	390 - 435	16	400	1	0,34	5,90
RG350169	445 - 495	18	450	2	0,34	8,75
RG350170	495 - 550	20	500	2	0,34	11,30
RG350171	515 - 555	21	525	2	0,21	11,30
RG350172	595 - 650	24	600	2	0,21	15,85

