



Double chain clamp

Clamping ranges: 203,2 - 1.524 mm (8 - 60")

- Max. Wall thickness: 12,7 mm
- The chain can be adapted to the respective pipe dimension by removing the chain links and alignment jack-bars

Part No.	Description	Range OD Inch	Range OD mm	Pieces jack-bars	Weight kg
RG350054		8 - 12	203 - 304	6	19,3
RG350055		8 - 16	203 - 406	7	20,9
RG350056		8 - 20	203 - 508	9	24,0
RG350057		8 - 24	203 - 609	11	27,2
RG350058		8 - 28	203 - 711	13	30,4
RG350059		8 - 32	203 - 812	14	32,0
RG350060	Double chain clamp	8 - 36	203 - 914	16	35,2
RG350061		8 - 40	203 - 1.016	18	38,4
RG350062		8 - 44	203 - 1.117	19	40,0
RG350063		8 - 48	203 - 1.219	21	43,1
RG350064		8 - 52	203 - 1.320	23	46,3
RG350065		8 - 56	203 - 1.422	25	49,5
RG350066		8 - 60	203 - 1.524	26	51,1

Accessories

for Double chain clamp

- Individual solutions through modular components

Part No.	Description	Weight kg
RG350075	Swivel for single chain	9,3
RG350076	Double jack-bar	0,9
RG350070	2-link chain	0,2
RG350071	3-link chain	0,3
RG350077	2-link chain with jack-bar	1,5
RG350078	3-link chain with jack-bar	1,6



2x 3-link chain with jack-bar
(177 mm length)



2x 2-link chain with jack-
bar (137 mm length)



Swivel



2-link chain



3-link chain