



Pipe clamp stainless steel

Clamping Range: 27 - 355 mm (1 - 14")

- For centering and aligning the pipes to be welded
- Easy assembly and centric clamping of the pipes
- Stainless steel contact points avoid corrosion
- Tensioning screws with stainless steel balls prevent scratching of stainless steel pipes

| Part No. | Description | Range OD Inch | Range OD mm | Weight kg |
|----------|--------------------------------------|------------------|----------------|--------------|
| RG350012 | Pipe clamp DWT SS13 stainless steel | 1 - 3 | 25 - 76 | 1,0 |
| RG350013 | Pipe clamp DWT SS26 stainless steel | 2 - 6 | 51 - 152 | 3,5 |
| RG350014 | Pipe clamp DWT SS614 stainless steel | 6 - 14 | 152 - 355 | 8,0 |

SPC External pipe clamp

Clamping Range: 10 - 140 mm (0.3 - 5.5")

- Each pipe side is centred by means of a crank
- Can align different pipe diameters with each other
- Stainless steel contact points



| Part No. | Description | Range OD Inch | Range OD mm | Weight kg |
|----------|---|------------------|----------------|--------------|
| RG350025 | External pipe clamps SPC1070 stainless steel | 0.3 - 2.7 | 10 - 70 | 2,0 |
| RG350026 | External pipe clamps SPC40140 stainless steel | 1.5 - 5.5 | 40 - 140 | 5,3 |