



## MF3-R


Clamping range OD-OD: 12 - 44,5 mm

The MF3-R is used for pipe end machining, i.e. for beveling individual pipes or membrane walls. Due to its compact design, the machine is particularly suitable for machining panel wall openings. The MF3-R can optionally be equipped with a pneumatic or an electric motor.

### Optional accessories



Tooling  
(from p. 32)



### Technical data

Working range ID-OD	9 - 44,5 mm	0,354 - 1,752"
Clamping range OD-OD	12 - 44,5 mm	0,472 - 1,752"
Max. wall-thickness	10 mm	0,393"
Feed	15 mm	0,590"
Weight with pneumatic motor	4,8 kg	10,6 lb
Weight with electric motor	6,0 kg	13,3 lb
Weld prep	facing, V-prep	
Materials	steel, stainless steel, duplex, high-alloyed	
Tooling	tool bits, TiN inserts, custom bits	
Machine body	lightweight housing	

### Available drives

#### Pneumatic motor

Power	850 W	1,2 HP
Air pressure	6 bar	87 psi
Air consumption	0,96 m <sup>3</sup> /min	33,9 cfm
Air hose connection	1/4"	
Features	speed control	

#### Electric motor

Power consumption	1.200W (110V/230V)	1,6 HP
Features	speed adjustment	